

	Type	L #	Hits	Search Text	DBs
1	BRS	L1	9876	battery and (coil inductor) and (diode rectific\$4) and reset	US-PGPUB; USPAT
2	BRS	L2	8561	1 and (below decreas\$3)	US-PGPUB; USPAT
3	BRS	L3	1264	2 and reset.clm.	US-PGPUB; USPAT
4	IS&R	L4	405	(307/130).CCLS.	US-PGPUB; USPAT
5	BRS	L5	28744	(coil inductor) and reset and (detect\$3 comparator) and below	US-PGPUB; USPAT
6	BRS	L6	32598	(coil inductor) and reset and (detect\$3 comparator) and (decreas\$ below)	US-PGPUB; USPAT
7	BRS	L7	31802	6 and (higher above boost\$3)	US-PGPUB; USPAT
8	BRS	L8	17355	7 and (diode rectifier)	US-PGPUB; USPAT
9	BRS	L9	7376	8 and battery	US-PGPUB; USPAT
10	BRS	L10	306	9 and (reset near4 (below decreas\$3))	US-PGPUB; USPAT
11	BRS	L11	219	10 not 3	US-PGPUB; USPAT
12	IS&R	L12	1211	(327/530).CCLS.	US-PGPUB; USPAT
13	IS&R	L13	1200	(327/536).CCLS.	US-PGPUB; USPAT
14	BRS	L14	863	13 and (compar\$3 detect\$3 monitor\$3)	US-PGPUB; USPAT
15	IS&R	L15	790	(327/143).CCLS.	US-PGPUB; USPAT
16	BRS	L16	81	15 and (charge adj pump boost\$3)	US-PGPUB; USPAT
17	BRS	L21	6	ir adj remote adj commander	US-PGPUB; USPAT
18	BRS	L22	12095	higher near2 (supply near2 (voltage power))	US-PGPUB; USPAT
19	BRS	L23	2724	22 and (coil inductor)	US-PGPUB; USPAT
20	BRS	L24	2005	23 and diode	US-PGPUB; USPAT
21	BRS	L25	1724	24 and (decreas\$5 below)	US-PGPUB; USPAT
22	BRS	L26	1643	25 and (off disable enable reset deactiva\$4 activat\$3)	US-PGPUB; USPAT
23	BRS	L29	342	(charge adj pump boost\$3) with ((detect\$3 comparat\$4) near3 output) with (stop\$3 reset disabl\$3 inactivat\$3 enabl\$3 activ\$3)	US-PGPUB; USPAT
24	IS&R	L30	327	(327/589).CCLS.	US-PGPUB; USPAT
25	IS&R	L32	875	(327/536).CCLS.	USPAT
26	BRS	L33	558	32 and diode	US-PGPUB; USPAT

	Type	L #	Hits	Search Text	DBs
27	BRS	L34	526	33 and capacitor	US-PGPUB; USPAT